AMENDMENTS TO THE CLAIMS

The listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS

Claim 1. (Currently Amended) A multiservice switching system, comprising:

a switching device, configured to establish connections over a network having predetermined functions with respect to a request for a predetermined service;

a switch controller having a bearer function and a virtual switch <u>control</u> function for controlling said switching device; and

a proxy device containing at least one of service policies that correlates service requests with respective services of a plurality of services to enable associated service policies and logic provided by a service controller, the proxy device implementing at least one of a service policy and logic related to one of enabling and denying said a requested predetermined service, in which multiple service requests are correlated with respective services to enable at least one appropriate policy and logic and initiating a connection to the network via the switch controller.

- Claim 2. (Original) The multiservice switching system of claim 1, wherein said switching device and said switch controller comprise a conventional switch.
- Claim 3. (Original) The multiservice switching system of claim 2, wherein said conventional switch comprises an ATM Switch.
- Claim 4. (Currently Amended) The multiservice switching system of claim 1, wherein said switching device and said switch controller comprise a next generation switch.
 - Claim 5. (Original) The multiservice switching system of claim 1, further comprising a

service controller, said service controller including said switch controller.

Claim 6. (Original) The multiservice switching system of claim 1, wherein said switching device includes said switch controller.

Claim 7. (Currently Amended) A method for switching plural forms of data, comprising:

Receiving, from an initiating customer, a request for at least one service of a plurality of services;

obtaining predetermined data related to the at least one requested service, the predetermined data correlating to at least one of a policy and logic corresponding to the requested service;

instructing the initiating customer to initiate a predetermined setup identifying the requested service, when the requested service is permitted and, in response to the predetermined setup, initiating a network connection based on the at least one respective appropriate policy and logic corresponding to the requested service;

passing a first predetermined signal across a network in response to the predetermined setup; initiating a second predetermined setup, in response to the passed first predetermined signal; passing a second predetermined signal across the network in response to the second predetermined setup, the second predetermined signal indicating whether to allow the network connection based on at least one of policy and logic of the network; and

providing to the initiating customer, in which multiple service requests are correlated with respective services to enable at least one appropriate policy and logic] a response indicating whether the network connection is allowed.

Claim 8. (Original) The method of claim 7, wherein obtaining comprises pushing the

predetermined data.

Claim 9. (Currently Amended) The method of claim 8, wherein the pushing predetermined data comprises pushing the at least one of policy and logic representing at least one of service capabilities and service permissions.

Claim 10. (Original) The method of claim 7, wherein obtaining comprises pulling the predetermined data.

Claim 11. (Original) The method of claim 7, wherein obtaining comprises querying a service control module for the predetermined data.

Claim 12. (Original) The method of claim 7, further comprising using a certificate to specify permitted setup parameters.

Claim 13. (Original) The method of claim 12, further comprising encrypting the certificate.

Claim 14. (Original) The method of claim 13, further comprising assigning a sequence number to the encrypted certificate.

Claim 15. (Original) The method of claim 12, wherein the certificate further identifies which service allowed the setup.

Claim 16. (Original) The method of claim 12, further comprising determining whether the certificate is valid.

Claim 17. (Original) The method of claim 12, further comprising preventing reuse of the certificate.

Claim 18. (Original) The method of claim 17, wherein preventing comprises examining a sequence number assigned to the certificate to determine whether the sequence number was seen before.

Claim 19. (Currently Amended) The method of claim 17, wherein preventing comprises examining at least one of a time-stamp and a date-stamp to determine wherein whether the at least one of the time-stamp and the date-stamp exceeds a predetermined delta value.

Claim 20. (Currently Amended) A method for switching plural forms of data through a network, comprising:

Receiving, at a service controller, a service request initiated by an initiating customer; obtaining predetermined data from the service controller related to at least one of policy and logic of the requested service;

establishing a network connection to the network using a first predetermined setup, initiated to realize the requested service, in which multiple-predetermined setups are correlated with respective services to enable corresponding in accordance with the at least one appropriate policy and logic of the service; and

initiating a second predetermined setup to one of accept and reject the requested network connection on behalf of the requested service and in accordance with at least one of policy and logic of the network.

Claim 21. (Previously Presented) The method of claim 20, wherein obtaining the predetermined data for the requested service comprises using a pushing procedure.

Claim 22. (Previously Presented) The method of claim 20, wherein obtaining the

predetermined data for the requested service comprises using a pulling procedure.

Claim 23. (Previously Presented) The method of claim 20, wherein obtaining the predetermined data for the requested service comprises using a query procedure.

Claim 24. (Previously Presented) The method of claim 20, further comprising requesting the initiating customer to initiate the predetermined setup as a user-to network interface setup.

Claim 25. (Currently Amended) The method of claim 20, the network comprising an ATM network, wherein establishing the network connection to realize the requested service comprises transferring the first predetermined setup over an the ATM network, the first predetermined setup being redirected from a switching device to a the service controller.

Claim 26. (Original) The method of claim 25, further comprising controlling the switching device with a switch controller, the switch controller being integral with the switching device.

Claim 27. (Original) The method of claim 25, further comprising controlling the switching device with a switch controller, the switch controller being integral with the service controller.

Claim 28. (Previously Presented) The method of claim 20, wherein obtaining the predetermined data for the requested service comprises providing a certificate for establishing the network connection in combination with the predetermined setup.

Claim 29. (Previously Presented) The method of claim 28, wherein the certificate specifies at least a permitted setup parameter.

Claim 30. (Original) The method of claim 28, further comprising encrypting the certificate.

Claim 31. (Original) The method of claim 30, further comprising assigning a sequence number to the encrypted certificate.

- Claim 32. (Previously Presented) The method of claim 28, wherein the certificate further identifies the requested service, which allowed the setup.
- Claim 33. (Original) The method of claim 28, further comprising determining whether the certificate is valid.
- Claim 34. (Original) The method of claim 28, further comprising preventing reuse of the certificate.
- Claim 35. (Original) The method of claim 34, wherein preventing comprises examining a sequence number assigned to the certificate to determine whether the sequence number was previously examined.
- Claim 36. (Original) The method of claim 34, wherein preventing comprises examining at least one of a time-stamp and a date-stamp to determine whether the at least one of the time-stamp and the date-stamp exceeds a predetermined delta value.
- Claim 37. (Currently Amended) The method of claim 7, wherein the predetermined setup comprises a UNI setup, the <u>first</u> predetermined signal comprises a PNNI protocol, and the second predetermined setup comprises a second UNI setup.
- Claim 38. (Original) The method of claim 20, wherein the predetermined setup comprises a user-to-network interface setup.
- Claim 39. (Previously Presented) A method for controlling customer access to capabilities of a network associated with a network service, the method comprising:
- receiving a request for the network service from a customer system at a service control distinct from a network connection capability of the network;

when the request is authorized, providing a certificate that specifies at least one permitted connection setup parameter related to the network service;

initiating a network connection setup request, associated with the network service, and providing the certificate; and

enabling a network connection in response to the network connection setup request based on the certificate and the at least one permitted connection setup parameter.

Claim 40. (Currently Amended) The method for controlling user access to capabilities of a the-network associated-with-a-network-service according to claim 39, the network comprising an ATM network.

Claim 41. (Currently Amended) The method for controlling user access to capabilities of a the network associated with a network service according to claim 39, the network comprising a packet switched data network.

Claim 42. (Currently Amended) The method for controlling user access to capabilities of a the network associated with a network service according to claim 39, further comprising encrypting the certificate.

Claim 43. (Currently Amended) The method for controlling user access to capabilities of a the network associated with a network service according to claim 39, further comprising preventing a repeat use of the certificate.

Claim 44. (Previously Presented) A method for controlling access to network capabilities associated with a network service, the method comprising:

providing a certificate in response to an authorized request for the network service, the

certificate specifying at least one permitted connection setup parameter related to the network service;

initiating a connection setup request associated with the network service based on the certificate, the connection setup request comprising a predetermined connection setup message;

routing the connection setup request through the network based on the certificate, the predetermined connection setup message and the at least one permitted connection setup parameter; and

allowing the connection setup request based on the certificate, the predetermined connection setup message and the at least one permitted connection setup parameter.

Claim 45. (Currently Amended) The method for controlling user access to capabilities of a the network associated with a network service according to claim 44, the certificate further specifying at least one of policy and logic of the network service.

Claim 46. (Currently Amended) The method for controlling user access to capabilities of a the network associated with a network service according to claim 44, the network comprising an ATM network.

Claim 47. (Currently Amended) The method for controlling user access to capabilities of a the network associated with a network service according to claim 44 the network comprising a packet switched data network.

Claim 48. (Previously Presented) A system for controlling user access to capabilities of a network associated with a network service, the system comprising:

a service controller that receives a request for the network service from a user system, determines whether the request for the network service is authorized and, when the request is authorized, provides a certificate that specifies at least one permitted connection setup parameter related to the network service; and

a network connection capability controller that receives the certificate and a connection setup request, the network connection capability initiating a network connection associated with the network service and enabling the network connection based on at least one of the connection setup request, the certificate and the at least one permitted setup parameter.

Claim 49. (Currently Amended) The system for controlling user access to capabilities of a the network associated with a network service according to claim 48, the network comprising an ATM network.

Claim 50. (Currently Amended) The system for controlling user access to capabilities of a the network associated with a network service according to claim 49 the network comprising a packet switched data network.

Claim 51. (Previously Presented) A method for controlling customer access to capabilities of a network associated with a network service, the method comprising:

receiving from a customer system a request for the network service;

instructing the customer system to perform a connection setup request, the instructing comprising specification of a unique identifier to be included in the connection setup request, the unique identifier correlating the connection setup request and the network service;

receiving from the customer system, at a network connection capability, the connection setup request, including the unique identifier;

processing the connection setup request based on the unique identifier and at least one of policy and logic associated with the network service; and

performing one of establishing a network connection and rejecting the connection setup request based on the processing, in accordance with the at least one of <u>service</u> policy and logic.

Claim 52. (Currently Amended) The method for controlling customer access to capabilities of a <u>the</u> network <u>associated with a network service</u> according to claim 51, wherein the <u>network requested</u> service pushes the at least one of <u>service</u> policy and logic into the network connection capability prior to instructing the customer system to perform a <u>the</u> connection setup request.

Claim 53. (Currently Amended) The method for controlling customer access to capabilities of a <u>the</u> network associated with a network service according to claim 51, wherein the network connection capability pulls in the at least one of <u>service</u> policy and logic from the <u>network requested</u> service after receiving the connection setup request.

Claim 54. (Currently Amended) The method for controlling customer access to capabilities of a the network associated with a network service according to claim 51, wherein the network service instructs the network connection capability regarding the processing of the connection setup request based on the at least one of service policy and logic from the network requested service and information regarding the connection setup request provided by the network connection capability in the form of a query.

Claim 55. (Currently Amended) The method for controlling customer access to capabilities of a the network associated with a network service according to claim 51, wherein the instructing further comprises a certificate to be included in the connection setup request;

wherein the processing the connection setup request is further based on the certificate; and wherein the performing one of establishing a network connection and rejecting the connection setup request is in further accordance with the certificate.

Claim 56. (Previously Presented) A system for controlling customer access to capabilities of a network associated with a network service, the system comprising:

a service controller that receives a request for the network service from a customer system and instructs the customer system to perform a connection setup request, the instructing comprising specification of a unique identifier to be included in the connection setup request, the unique identifier correlating the connection setup request and the network service; and

a network connection capability controller that receives the connection setup request, including the unique identifier, from the customer system;

wherein the network connection capability controller processes the connection setup request based on the unique identifier and at least one of policy and logic associated with the network service, and performs one of establishing a network connection and rejecting the connection setup request based on the processing, in accordance with the at least one of policy and logic.

Claim 57. (Currently Amended) The system for controlling customer access to capabilities of a the network associated with a network service according to claim 56, wherein the service controller

pushes the at least one of policy and logic into the network connection capability controller prior to instructing the customer system to perform a connection setup request.

Claim 58. (Currently Amended) The system for controlling customer access to capabilities of a the network associated with a network service according to claim 56, wherein the network connection capability controller pulls in the at least one of policy and logic from the service controller after receiving the connection setup request.

Claim 59. (Currently Amended) The system for controlling customer access to capabilities of a the network associated with a network service according to claim 58, wherein the service controller instructs the network connection capability controller regarding the processing of the connection setup request based on the at least one of policy and logic and on information from the connection setup request provided by the network connection capability controller in the form of a query.

Claim 60. (Currently Amended) The system for controlling customer access to capabilities of a <u>the</u> network associated with a network service according to claim 56, wherein the service controller further instructs a certificate to be included in the connection setup request;

wherein the network connection capability controller processes the connection setup request further based on the certificate; and

wherein the network connection capability controller performs one of establishing a network connection and rejecting the connection setup request in further accordance with the certificate.